

DX6i Program Settings/Values for Blade 400 3D RTF*

*NOTE - All DX6i settings are the same as "default" unless specified otherwise below

ADJUST LIST					
D/R&EXPO					
AILE	1	90%	INH		
ELEV	1	90%	INH		
TRAVEL ADJ					
RUDD	<- 90%	->	90%		
GYRO					
RATE	SW- GYRO				
0:	66.5%				
1:	64.0%				
THRO CUR					
STUNT	POS L	POS 2	POS 3	POS 4	POS H
	100.0%	92.5%	85.0%	92.5%	100.0%
HOLD	POS H				
	- 0.0%				
PITC CUR					
NORM	POS L	POS 2	POS 3	POS 4	POS H
	35.0%	42.5%	50.0%	75.0%	100.0%
HOLD	POS L	POS 2	POS 3	POS 4	POS H
	35.0%	42.5%	50.0%	75.0%	100.0%
SWASH MIX					
AILE	- 75%				
ELEV	- 75%				
PITC	+ 85%				
SETUP LIST					
MODEL NAME					
MODEL 1					
BLADE400					
REVERSE					
AILE - R					
RUDD - R					
SWASH TYPE					
CCPM	120*				
TIMER					
DOWN TIMER - 04:30					